

Section I. Product Identification and Uses

**HMIS (HFRP)**  
**Health Hazard** 3  
**Fire Hazard** 3  
**Reactivity** 0  
**Personal Protection** b

<b>Common / Trade name</b>	BAN-O Liquid Deodorant	<b>TDG</b>	CLASS 3
<b>WHMIS</b>	B2, D1B, D2A, D2B	<b>PIN</b>	UN1170 ETHANOL SOLUTION
<b>Code</b>	2000	<b>PG</b>	III
<b>Material uses</b>	Liquid deodorant.		

Section II. Hazardous Ingredients

Name	CAS #	% by weight	TLV/PEL	LC50/LD50
Ethanol	64-17-5	15 - 40	Not available.	ORAL (LD50): Acute: 13700 mg/kg [Rat].
Isopropyl alcohol	67-63-0	10 - 30	Not available.	ORAL (LD50): Acute: 3600 mg/kg [Mouse]. > 4720 mg/kg [Rat].
Methanol	67-56-1	3 - 7	ACGIH (Canada). TWA: 200 mg/m <sup>3</sup> STEL: 250 mg/m <sup>3</sup> CEIL: 200 mg/m <sup>3</sup>	ORAL (LD50): Acute: 6200 mg/kg [Rat]. 7300 mg/kg [Mouse]. DERMAL (LD50): Acute: 15800 mg/kg [Rabbit]. VAPOR (LC50): Acute: 64000 ppm 4 hour(s) [Rat].
Polyethylene glycol (5) Undecyl ether	34398-01-1	1 - 5	Not available.	Not available.

Section III. First Aid Measures

**Eye contact** IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. If irritation persists, get medical attention.

**Skin contact** Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Cover the irritated skin with an emollient. If irritation persists, seek medical attention. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes.

**Inhalation** Allow the victim to rest in a well ventilated area. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

**Ingestion** If ingested do not induce vomiting. Have conscious person drink several glasses of water. Get medical attention immediately.

Section IV. Physical Data

<b>Physical state and appearance</b>	Liquid.	<b>Colour</b>	Slightly turbid to colorless.
<b>pH (1% soln/water)</b>	Not available	<b>Odour</b>	Lime.
<b>pH (concentrate)</b>	Not applicable	<b>Volatility</b>	Not available.
<b>Boiling point</b>	The lowest known value is 65°C (149°F) (Methyl Alcohol).	<b>Vapour density</b>	Not available.
<b>Specific gravity</b>	0.90-0.91 (Water = 1)	<b>Vapour pressure</b>	The highest known value is 12.9 kPa (97 mm Hg) (at 20°C) (Methyl Alcohol).
<b>Solubility</b>	Easily soluble in cold water, hot water.		

Section V. Fire and Explosion Data

**The product is** Flammable.

**Auto-ignition temperature** The lowest known value is 385°C (725°F) (Methyl Alcohol).

**Flash points** Closed cup: 24°C (75.2°F).

**Degradation products** These products are carbon oxides (CO, CO2).

**Extinguishing media** Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemicals, CO2, alcohol foam or water spray. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Section VI. Reactivity data

**Stability** The product is stable.

**Decomp. products** Carbon oxides (CO, CO2).

**Reactivity** Reactive with oxidizing agents, acids.

**Section VII. Toxicological properties**

**Route of entry** Ingestion. Skin contact. Inhalation. Eye contact.

**Toxicity for animals** Acute oral toxicity (LD50): 6200 mg/kg (Rat) (Calculated value for the mixture). Acute toxicity of the gas (LC50): > 5000 ppm (Rat) (Isopropyl alcohol). Acute toxicity of the vapor (LC50): > 5000 ppm (Rat) (Ethanol).

**Acute effects** Aspiration hazard if swallowed. Harmful by inhalation, in contact with skin and if swallowed. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. This product is a eye irritant. This product may irritate skin upon contact.

**Chronic effects** No ingredient in this product is currently listed as carcinogens by IARC, NTP or OSHA. The substance (ethanol) is toxic to the reproductive system.

---

**Section VIII. Preventive measure**

**Waste disposal** Dispose of material according to regional, provincial and federal regulations. Consult your local or regional authorities.

**Storage** Keep away from heat, from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. A refrigerated room would be preferable for materials with a flash point lower than 37.8°C (100°F).

**Precautions** Keep away from heat, from sources of ignition. DO NOT ingest. Do not breathe gas, fumes, vapor or spray. Avoid contact with skin and eyes. Keep out of reach of children. Keep away from incompatibles.

**Spill and leak** Eliminate all sources of ignition and ventilate the area. Absorb with an inert material and place in an appropriate waste disposal container. Finish cleaning the spill area with running water. Dispose of in accordance with federal, provincial, or local regulations.

---

**Section IX. Personal protective equipment**

**Gloves** Gloves (impervious).

**Respiratory** Wear appropriate respirator when ventilation is inadequate.

**Eyes** Safety glasses.

**Other** Full suit, apron, face shield, boots: are recommended under exceptional circumstances such as fire or spill.

**Eng. controls** Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

---

**Section X. Preparation and other Information**

Validated by the Regulatory Affairs Department on July 15th 2011

Printed 13 Feb. 2012

**EMERGENCY: CANUTEC 613-996-6666**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

---

**Annex A. Legend**

**HMIS** Hazardous Materials Identification System

**WHMIS** WHMIS Workplace Hazardous Materials Information System

**TDG** Transport Dangerous Goods

**PIN** Product Identification Number

**PG** Packaging Group

---